

## Industry's advantage with Hydrovane



# ©hydrovane

Rotary Vane Air Compressors

## The right compressor for your business

### Versatile

#### Open and enclosed format packages and air end options

- 50 / 60 Hz
- 6 - 10 bar
- 0.1 - 7.5 m<sup>3</sup>/min
- 4 - 264 cfm

#### Quiet as standard

With noise levels as low as 62 dB(A) a Hydrovane can be located at the point of use.

#### Fixed and Regulated speed models

Matching air demand with your business needs.

### Reliable by Design

#### Direct drive

No gears. No belts. Up to 100,000+ operating hours due to its simple integral design.

#### High quality air

Clean, dry and pulse free straight from the outlet means less downstream equipment required.

#### Slow speed

1450 - 1760 rpm speed operation results in low noise, low stresses and long life.

#### Common replacement parts

Quick, cost-effective servicing, with minimal downtime.

### Powerful and Cost Effective

#### Hydrovane Pro Controller

For total electronic control, greater connectivity and flexibility.

#### Regulated speed

Proven, simple and long-lasting technology solutions delivering up to 50% energy savings.

#### Reduced Energy Venting System (REVS)

Reducing off-load power to as low as 20%.

#### Air Intake modulation control

No wasteful overproduction of air.

### Guaranteed

#### Market leading warranty

Up to 10 years or 48,000 operating hours is now available for total peace of mind on all standard Hydrovane models.

#### J & J Air Systems Distributor support

J&J Air Systems are one of the largest and most experienced Hydrovane stockists in the UK. Our factory-trained Engineers are Authorised by Hydrovane for the Supply; Installation; Maintenance including 10 Year Advanced Warranty support.



# A range of compressors

## From stand-alone...

### Open - Fixed Speed

Small and compact, Hydrovane HV01 - HV04 models are ideally suited for light industrial and workshop applications where the compressed air outlet needs to be situated close to the point of use.

### HV01 - HV04 Models

Tripod or Receiver mounted

- 50 / 60 Hz
- 1.1 - 4 kW
- 10 bar
- 0.1 - 0.6 m<sup>3</sup>/min
- 4 - 20 cfm



### Enclosed - Fixed Speed and Regulated Speed (RS)

Taking components that have been developed specifically with energy-saving in mind, Hydrovane's designers and engineers have developed a rotary vane compressor for the twenty first century, whilst retaining the features which have helped build Hydrovane's reputation for quality and reliability around the world.

### HR04 - HR07RS Models

Fully Enclosed

- 50 / 60 Hz
- 4 - 7.5 kW
- 7 - 10 bar
- 0.6 - 1.3 m<sup>3</sup>/min
- 20 - 46 cfm



Whilst all Hydrovane rotary vane compressors are designed and built with the highest levels of efficiency in mind, if you're looking for the ultimate in energy-saving technology, we offer our 7.5 to 45 kW machines with a Regulated Speed (RS) option.

RS machines optimise energy efficiency when operated below full load capacity. This can deliver benefits of up to 50% energy savings compared to the equivalent standard fixed speed model.

### HV11 - HV45RS Models

Fully Enclosed

- 50 / 60 Hz
- 11 - 45 kW
- 6 - 10 bar
- 1.3 - 7.5 m<sup>3</sup>/min
- 46 - 264 cfm



# ...to the complete compressed air solution

Complete packages save space. Save time.

Hydrovane compressors are available as fully integrated packages. Hypacs are available with membrane or refrigerant dryers and integrated receivers and come as a factory built package or can be supplied as a kit for local assembly.

**Integrated packages can be more cost- effective than building a system using separate components.**

Hydrovane's knowledgeable Authorised Distributors can advise you on the best package for your business to make the most of factory space and give you more for your budget.

## Hypac Open – Fixed Speed

### HV01 – HV04 Models

#### Receiver Mounted

- Integrated Membrane Dryer
- 50 / 60 Hz
- 4 - 7.5 kW
- 10 bar
- 0.1 - 0.6 m<sup>3</sup>/min
- 4 - 20 cfm



## Hypac Enclosed – Fixed Speed and Regulated Speed (RS)

### HR04 – HV22RS Models

#### Fully Enclosed

- Integrated Refrigerant Dryer model
- Integrated Receiver model
- 50 Hz
- 4 - 22 kW
- 7 - 10 bar
- 0.6 - 3.6 m<sup>3</sup>/min
- 20 - 127 cfm



Make your budget go further

**Hydrovane Air Solution packages are the ultimate in convenience.**

Fully packaged with integrated receivers, refrigerant dryers and filtration, Hydrovane Air Solution models offer you the best solution for your compressed air requirements.



## Air Solution Enclosed – Fixed Speed and Regulated Speed (RS)

### HR04 – HV22RS Models

#### Fully Enclosed. Fully Packaged

- Complete Package
- Integrated Refrigerant Dryer
- Integrated Receiver
- Filter Pack
- 50 Hz
- 4 - 22 kW
- 6 - 10 bar
- 0.6 - 3.6 m<sup>3</sup>/min
- 20 - 127 cfm





At the heart of your  
compressor's performance

# Hydrovane Pro puts you in complete control

HR04 - HV45RS Models

## Hydrovane Pro Controller Features:

- Real Time Clock
- Timer Control
- Second Pressure Setting
- Status Display
- Group Fault Outputs
- Error Logs
- Digital Inputs
- MODBUS RTU
- Sequencer Capability
- Flash Programmable



with simple-to-use, intelligent electronics

All Hydrovane compressors in both Fixed and Regulated Speed in the 4 to 45 kW model range are fitted as standard with the Hydrovane Pro Electronic Controller. This control system ensures reliable operation and protects your investment by continuously monitoring the operational parameters of the compressor.

The Hydrovane Pro also has the capability to have programmable inputs and outputs for increased control of ancillary equipment.

It is now possible to simply connect a Hydrovane Pro controlled compressor to the range of Sequencer Technologies within the Gardner Denver group allowing flexibility of use and maximising energy reduction.

## HV01, HV02 and HV04 Models Standard Starters

A high quality srarter with a robust control circuit, including over-temperature protection.







## Reduce your energy costs

### How does a Hydrovane compressor save energy?

#### Regulated Speed (RS)

- RS control ensures optimum load conditions throughout the compressor's speed range  
**Delivering maximum efficiency**

#### Air Intake Modulation

- Air intake modulation at minimum speed delivers further energy savings  
**To match the reducing air demand**

#### Reduced Energy Venting System (REVS)



- In-built Reduced Energy Venting System (REVS)  
**Improved part-load and off-load performance**

#### SMART SERVO energy reduction system

- Optimised motor, drive and air end  
**Proven air cooled inverter drive**  
**High efficiency across a broad flow range**  
**Substantial energy savings delivered.**

Please contact your local authorised Hydrovane distributor for an Air System Energy Review and Data Logging.

**Reduce the cost of ownership and minimise your energy consumption.**





## Customise your Hydrovane

### to suit your applications

With Hydrovane's versatile rotary vane compressor technology, we can deliver the widest range of bespoke OEM solutions.

The possibilities are endless when it comes to supplying air for a specific application inside and outside the standard industrial arena. Hydrovane has over 50 years experience in supplying proven solutions to OEMs, either as air ends or complete packages, designed and purpose built. In addition, there are occasions when a customer may require a special build, and this is where Hydrovane can deliver custom solutions.



**Air Cooled Compressor Arrangement**

For Part Numbers refer to Drawing AV04-ATSN-xx

Performance @ 1450 rpm:  
 - 500\* l/min @ 10 bar  
 - 350\* l/min @ 12 bar  
 Max Working Pressure: 12 bar  
 Ambient: 40°C max  
 Mass: 75\* kg (approximately)

\* Compressor stator and motor type will be selected to suit specific flow/pressure requirements and ambient conditions. Motor dimensions/weight may vary.

\*\* Inlet Air Cleaner can be supplied as a loose item or mounted on a bracket on the end of the frame. Air Inlet adapter can be rotated through 30° increments to suit the application.





# Hydrovane Advance™10

Warranty that delivers complete peace of mind



## Hydrovane standard warranty:

All Hydrovane compressors are guaranteed for 12 months from the date of installation providing the installation is approved by an authorised Hydrovane distributor and the correct service procedures and genuine service kits, parts and lubricants are used.

The Hydrovane Advance 10 extended warranty programme is a unique market leading compressor care package designed to deliver comprehensive warranty cover for up to 10 years or 48,000 operating hours on all Hydrovane compressor airends.

## Key benefits

- ➔ Free
- ➔ Guaranteed Quality
- ➔ Accurate Maintenance Budgeting
- ➔ Maximise Compressor Life
- ➔ Simple administration
- ➔ Hydrovane will give you an appropriate service schedule
- ➔ Trained and qualified engineers will take care of your machines.

NOTE: Terms and conditions apply to all Advance 10 Warranty offers. Please consult your local Authorised Hydrovane Distributor for details.

## We're the professionals

Hydrovane's distributors will visit your site, free of charge, to assess your individual compressed air requirements in order to deliver the solution that best meets your requirements.

# Your local Hydrovane distributor

Sales and Aftermarket Support. Back-up you can trust

Hydrovane service philosophy is one of regular maintenance being the key to long, reliable, trouble-free compressor life. Hydrovane offers extensive aftermarket support through an extensive network of Authorised Distributors who will provide:

### FREE energy surveys

To test your compressed air system for possible leaks and other costly inefficiencies

### Service Kits - Genuine OEM spare parts

The service kit concept has been developed to make our compressor servicing quick, easy and cost effective. Using the service kits as part of the recommended service schedule will prevent costly breakdowns, ensuring a continuous supply of high quality compressed air.

### Lubricants - Approved for vane usage

Even the most reliable compressors in the world require routine lubricant changes to maintain peak performance. Over many years, Hydrovane has developed a range of high quality lubricants that have been specifically formulated to guarantee optimum compressor performance.

### Factory-trained service engineers

Hydrovane is committed to providing every Hydrovane compressor owner with fully trained Service Engineers to care for their investment throughout our Global Distribution Network.



Look after your Hydrovane and it will last a lifetime





# 50 / 60 Hz Rotary Vane Air Compressors

## Open - Fixed Speed



Motor Power (kW)	Model	Voltage/Phase		Starter Type	Configuration	Receiver Capacity (litres)	Maximum FAD m³/min (cfm)	Dimensions (mm)			Noise dB(A)	Air Quality (mg/m³)
		50Hz	60Hz				10 bar	Depth	Width	Height		
1.1	HV01	240V 1Ph 400V 3Ph	-	DOL	Tripod Mounted	-	0.12 (4.3)	270	700	470	62	<3
1.5	HV01	-	230V 1ph 230V 3ph 460V 3ph				0.14 (4.9)				65	
2.2	HV02	240V 1Ph 400V 3Ph	-				0.23 (8.0)				69	
1.1	HV01	240V 1Ph 400V 3Ph	-		Receiver Mounted	75	0.12 (4.3)	300	1120	730	62	
1.5	HV01	-	230V 1ph 230V 3ph 460V 3ph				0.14 (4.9)				65	
2.2	HV02	240V 1Ph 400V 3Ph	-				0.23 (8.0)				69	
4.0	HV04RM	400V 3Ph	-				0.57 (20.1)				73	
5.5	HR05PR	400V 3Ph	-	SD	Receiver Mounted	200	0.71 (25.1)	570	1332	1068	73	<3
7.5	HR07PR						1.00 (35.0)					

## Regeneration 50 Hz Enclosed - Fixed and Regulated Speed



Motor Power (kW)	Model	Voltage/Phase	Starter Type	Maximum FAD m³/min (cfm)		Dimensions (mm)			Noise dB(A)	Air Quality (mg/m³)
				7 bar	10 bar	Depth	Width	Height		
4.0	HR04E	400V 3Ph	SD	0.68 (24.0)	0.57 (20.1)	695	630	1078	66	<3
5.5	HR05E			0.91 (32.1)	0.71 (25.1)				67	
7.5	HR07E			1.25 (44.1)	1.00 (35.0)				67	
7.5	HR07E RS	400V 3Ph	V	-	0.97 (34.3)	695	630	1078	70	<3

## Enclosed - Fixed Speed



Motor Power (kW)	Model	50Hz		60Hz		Maximum FAD m³/min (cfm)				Dimensions (mm)			Noise dB(A)	Air Quality (mg/m³)
		Voltage/Phase	Starter Type	Voltage/Phase	Starter Type	50Hz		60Hz		Depth	Width	Height		
						8 bar	10 bar	8 bar	10 bar					
11.0	HV11	400V 3Ph	SD	460V 3Ph 575V 3Ph	DOL	1.63 (57.6)	1.41 (49.8)	1.48 (52.4)	1.29 (45.6)	850	700	1550	69	<3
15.0	HV15					2.21 (78.1)	2.01 (71.0)	1.90 (67.1)	1.65 (58.4)				70	
18.0	HV18					2.88 (101.7)	2.55 (90.1)	2.80 (99.0)	2.44 (86.2)				71	
22.0	HV22					3.60 (127.1)	2.96 (104.5)	3.25 (114.6)	2.83 (100.0)	1130	900	1640	73	
30.0	HV30					5.00 (176.6)	4.31 (152.2)	4.43 (156.5)	3.86 (136.2)					
37.0	HV37					5.95 (210.1)	5.07 (179.0)	5.48 (193.7)	4.77 (168.5)					
45.0	HV45					7.33 (258.9)	6.54 (231.0)	6.54 (231.0)	5.73 (202.3)					

Note: The 50 Hz / 400 Volts / 3 Phase Regulated Speed (RS) models also cover 60 Hz / 460 Volts / 3 Phase

## Enclosed - Regulated Speed (RS)



Motor Power (kW)	Model	Voltage/Phase		Starter Type	Maximum FAD m³/min (cfm)			Dimensions (mm)			Noise dB(A)	Air Quality (mg/m³)
		50Hz	60Hz		6 bar	8 bar	10 bar	Depth	Width	Height		
11.0	HV11RS	400V 3Ph	460V 3Ph	V	1.74 (61.6)	1.56 (55.0)	1.37 (48.5)	850	700	1550	69	<3
15.0	HV15RS				2.29(80.8)	2.03 (71.6)	1.72 (60.7)				70	
18.0	HV18RS				2.96 (104.6)	2.75 (96.9)	2.51 (88.5)				71	
22.0	HV22RS				3.53 (124.5)	3.22 (113.8)	3.07 (108.3)	1130	900	1640	73	
30.0	HV30RS				5.38 (189.9)	4.87 (171.9)	4.51 (159.3)				73	
37.0	HV37RS				6.17 (217.8)	5.72 (202.1)	5.27 (186.1)				73	
45.0	HV45RS				7.47 (263.7)	6.90 (243.5)	6.51 (230.0)				73	

## Hypac 50 Hz Enclosed



Motor Power (kW)	Model		Configuration	Voltage/Phase	Starter Type	Receiver Capacity (litres)	Package Dimensions (mm)			Pressure Dew Point (°C)	Air Quality (mg/m³)		
							Depth	Width	Height				
4.0	HR04	HRER	Integrated Receiver	400V 3Ph	SD / V	260	695	1220	1692	8	<3		
5.5	HR05												
7.5	HR07 / HR07RS											HRER / RS	
11	HV11 / HV11RS	HVER / RS				272	1187	1355	1550		<2		
15	HV15 / HV15RS												
18	HV18 / HV18RS												
22	HV22 / HV22RS												
4.0	HR04	HRED	Integrated Refrigerant Dryer	400V 3Ph	SD / V	-	984	630	1078	3	<1		
5.5	HR05												
7.5	HR07 / HR07RS	HRED / RS					825	1215	1550				
11	HV11 / HV11RS	HVED / RS											
15	HV15 / HV15RS												
18	HV18 / HV18RS												
22	HV22 / HV22RS												

## Air Solution 50 Hz - The Complete Package



Motor Power (kW)	Model		Configuration	Voltage/Phase	Starter Type	Receiver Capacity (litres)	Package Dimensions (mm)			Pressure Dew Point (°C)	Air Quality (mg/m³)
							Depth	Width	Height		
1.1	HVO1RM	AERD	Receiver Mounted + Membrane Dryer	240V 1ph or 400V 3Ph	DOL	75	300	1120	730	30*	<1
2.2	HVO2RM					200	455	1410	990		
4.0	HVO4RM					200	455	1410	990		
4.0	HR04	AERD	Integrated Refrigerant Dryer & Receiver	400V 3Ph	SD / V	260	984	1220	1692	3	<1
5.5	HR05										
7.5	HR07 / HR07RS	AERD / RS				272	1187	1355	1550	3	<1
11	HV11 / HV11RS										
15	HV15 / HV15RS										
18	HV18 / HV18RS										
22	HV22 / HV22RS										

Note: The only 60 Hz model available is the HV01RM

### Starter Types:

- DOL Direct On Line
- SD Star Delta
- V Regulated Speed (RS)

Free Air Delivered (FAD) according to BS ISO1217:2009-Annex B, C and E  
\*Both fixed speed and regulated speed compressors operate between 0°C and 45°C ambient.  
Hydrovane compressors are designed for indoor installation under cover only.  
Contact your Hydrovane Distributor for applications outside these conditions.



# Global experience – truly local service



Our Sales and Service trade counter in High Wycombe.

With over 200 years of combined engineering excellence, the Hydrovane range, part of the Compair brand offers an extensive range of highly reliable, energy efficient compressors and accessories to suit all applications.

An extensive network of dedicated CompAir Sales companies across all continents provide global expertise with a truly local service, ensuring our advanced technology is backed up with the right support.

As part of the worldwide Gardner Denver operation, CompAir has consistently been at the forefront of compressed air systems development, culminating in the most energy efficient and low environment impact Air Compressors on the market today, helping customers achieve or surpass their sustainability targets.

## CompAir and Hydrovane compressed air product range

### Advanced Compressor Technology Lubricated

- Rotary Vane and Rotary Screw
  - > Fixed and Regulated Speed
- Piston
- Portable

### Oil-Free

- Water Injected Screw
  - > Fixed and Regulated Speed
- Two Stage Screw
  - > Fixed and Regulated Speed
- Piston
- High Speed Centrifugal - Quantima
- Rotary Scroll

### Complete Air Treatment Range

- Filtration
- Refrigerant and Desiccant Dryer
- Condensate Management
- Heat of Compression Dryer
- Nitrogen Generator

### Modern Control Systems

- CompAir DELCOS Controllers
- SmartAir Master Sequencer

### Value Added Services

- Professional Air Audit
- Performance Reporting
- Leak Detection

### Leading Customer Support

- Custom Engineered Solutions
- Genuine CompAir Parts and Lubricants



**J&J Air Systems**



J&J Air Systems  
Sands Industrial Estate,  
High Wycombe  
Bucks HP12 4HJ  
United Kingdom

Customer Service: 0800 027 8442  
Telephone: 01494 530291  
International: +44 (0)1494 530291  
Fax: +44 (0)1494 463062

[sales@JJAirSystems.co.uk](mailto:sales@JJAirSystems.co.uk)  
[www.JJAirSystems.co.uk](http://www.JJAirSystems.co.uk)